



CONCRETE/TERRAZZO


WALL CHART

Level 2 - Semi-Polish Ongoing Maintenance

One pad & one cleaning chemical
Optional stain protection



ES37
Cleaner Maintainer Polisher 1:128



800 Grit CMP Pad

STEP 1



Sweep the floor with a dry mop to remove all loose soils and debris.

STEP 2



Fill the solution tank with **ES37 Cleaner Maintainer Polisher** by using a dilution control system to ensure proper dilution every time.

> **Enviro-Solutions®** Product Code: **LSP29-B4 LavoDose 1 Button** (wall mount dispenser)

If you do not have a dilution control system, fill the solution tank with water first then pour the appropriate amount of **ES37 Cleaner Maintainer Polisher** into the tank.

Dilution ratio is 1:128 (1 oz of **ES37** / 1 gallon of water) (7.8 mL of **ES37** / 1 L of water)

> Example: a 10-gallon solution tank will need 10 oz of **ES37**

Recommended Tip



Dispenser Code: **LSP29-B4**

We recommend installing our "Plug & Play" wall mounted dispenser for worker dilution convenience and best results.

STEP 3



Affix **ES-CMP 800 Grit Diamond Pad(s)** to center lock pad driver(s) making sure the pad(s) have no wrinkles and are secure on the driver(s).

Transport machine to the area to be scrubbed and plan the most appropriate scrub path for the floor.

STEP 4



Turn on solution valve to max flow and lower the pads to the floor

Turn on vacuum motor, lower squeegee and commence scrub path pattern.

Overlap each pass slightly to ensure the floor is covered completely with no gaps.

Adjust solution flow rate and scrub skirt to ensure no flooding or splashing has occurred.

STEP 5



At the end of the cleaning cycle return the machine to acceptable slop sink and empty dirty water reservoir.

Remove **Enviro-Solutions® CMP Pads** and rinse them off to clear them of any debris that may have been collected on the pad.