




# CONCRETE/TERRAZZO WALL CHART

## Level 3 - Polish Ongoing Maintenance

One pad & one cleaning chemical  
Optional stain protection



**ES37  
Cleaner Maintainer Polisher 1:128**



**3000 Grit CMP Pad**

### STEP 1



Sweep the floor with a dry mop to remove all loose soils and debris.

### STEP 2



Fill the solution tank with **ES37 Cleaner Maintainer Polisher** by using a dilution control system to ensure proper dilution every time.  
> **Enviro-Solutions®** Product Code: **LSP29-B4 LavoDose 1 Button** (wall mount dispenser)

If you do not have a dilution control system, fill the solution tank with water first then pour the appropriate amount of **ES37 Cleaner Maintainer Polisher** into the tank.

Dilution ratio is 1:128 (1 oz of **ES35** / 1 gallon of water) (7.8 mL of **ES35** / 1 L of water)

> Example: a 10-gallon solution tank will need 10 oz of **ES37**

### Recommended Tip



Dispenser Code: **LSP29-B4**

We recommend installing our "Plug & Play" wall mounted dispenser for worker dilution convenience and best results.

### STEP 3



Affix **ES-CMP 3000 Grit Diamond Pad(s)** to center lock pad driver(s) making sure the pad(s) have no wrinkles and are secure on the driver(s).

Transport machine to the area to be scrubbed and plan the most appropriate scrub path for the floor.

### STEP 4



Turn on solution valve to max flow and lower the pads to the floor

Turn on vacuum motor, lower squeegee and commence scrub path pattern.

Overlap each pass slightly to ensure the floor is covered completely with no gaps.

Adjust solution flow rate and scrub skirt to ensure no flooding or splashing has occurred.

### STEP 5



At the end of the cleaning cycle return the machine to acceptable slop sink and empty dirty water reservoir.

Remove **Enviro-Solutions® CMP Pads** and rinse them off to clear them of any debris that may have been collected on the pad.

### STEP 6: Optional Dry Brushing



Affix **ES-CMP 3000 Grit Diamond Pad** to center lock pad driver making sure the pad has no wrinkles and is secure on the driver.

Burnish the entire floor with the **ES-CMP 3000 Grit Diamond Pad**.

Sweep the floor with a dry mop to remove all loose soils and debris.

### Recommended Tip



If there is a desire to achieve a higher sheen, we recommend having a good operating burnishing that uses 17, 20 or 27 inch diameter pads. It can be electric, battery or propane powered.

In the event more sheen is needed please consult a Charlotte Products expert. In some cases a polished concrete or terrazzo penetrating guard can be applied to offer extended protection and enhanced sheen.