



# DURAFLEX

## FLOOR FINISH

### Features & Benefits:

- HIGH TRACTION
- HIGH DURABILITY
- PROVIDES GREATER COEFFICIENT OF FRICTION ON MULTIPLE SUBSTRATES
- 22% SOLIDS FINISH

### Description:

Custom Solutions™ Duraflex is a special polymer combination that enhances gloss, durability and slip resistance. Perfect for gym floors and hallways or any other place where a high coefficient of friction is required.

### Directions:

First time application

1. Prepare the floor utilizing a Custom Solutions™ floor stripper. Completely remove all previously used floor coatings, follow stripping directions.
2. Thoroughly rinse floors with clean water after stripping or deep scrubbing before applying finish.
3. Apply 4 - 6 coats of Duraflex Floor Finish with a rayon finish mop or applicator. Allow at least 30 minutes between coats. On porous resilient or stone floors, first seal with 2 coats of a Custom Solutions™ Sealer or apply 2 extra coats of Duraflex.
4. Let dry thoroughly.

Scrub and Recoat

1. Dry mop area.
2. Scrub thoroughly using a blue pad, with Code Blue.
3. Apply 1-2 new coats of Custom Solutions™ Duraflex Floor Finish.

Maintenance

1. Dry mop daily.
2. Clean with Clarity Neutral Floor Cleaner

### Specifications:

**pH:** 8.5

**Colour:** Opaque white

**Fragrance:** Polymer

### Product Code:

319016-18 (2x2.5 U.S. Gal.)



Market Segments: 

**Building Service Contractor, Education, Healthcare, Recreation, Retail**



2060 Fisher Drive,  
Peterborough, Ontario  
K9J 8N4

Tel: 705.740.2880  
Fax: 705.745.1239  
Toll Free: 1.877.745.2880  
Web: [www.charlotteproducts.com](http://www.charlotteproducts.com)